

PRODUCT: _____ QUANTITY: _____ ITEM: _____ Models ML HML2,3,4

Designed Smart

Bid Specifications

Mobile enclosed, field adjustable Dish Dispenser features heavy-duty stainless steel frame construction. The dispensing mechanism in APW Wyott's Lowerators® uses springs attached to a sliding support bar that rides both inside and outside the tube. This design feature prevents a stack of dishware from sticking in the down position, and releasing unexpectedly. All contact edges are protected by heavy-gauge stainless steel with black rubber perimeter bumpers. Available in heated or unheated models. Unit has 4" polyurethane swivel casters, two with brakes.

Applications

Mobile enclosed cabinet-style Dish Dispenser utilizes Adjustube® self-leveling tubes that are field adjustable for weight. Holds and dispenses plates, saucers, or bowls. Hole cutouts in base align lower end of tubes in position to prevent movement during transit. Field adjustable for varying weight loads up to 100 lbs. per tube. Available in two and three-stack units, heated and unheated models.

APW Wyott Design Features

- Promotes sanitary conditions.
- Provides finished appearance.
- Easy handling of dishware.
- Maximum stability and rigidity of unit.
- Dispensing tubes are removable for cleaning.

Reliability backed by APW Wyott's Warranty

All APW Wyott Lowerators are backed by a 1-year limited warranty and a 1-year on-site labor warrant. *

•Certified by the following agencies:



Model: Lowerator® Enclosed Mobile Dispensers

Models

- | | | | |
|----------------------------------|---------------------------------|-----------------------------------|----------------------------------|
| <input type="checkbox"/> ML2-5 | <input type="checkbox"/> ML2-6 | <input type="checkbox"/> ML2-6.5 | <input type="checkbox"/> ML2-7 |
| <input type="checkbox"/> ML2-8 | <input type="checkbox"/> ML2-9 | <input type="checkbox"/> ML2-10 | <input type="checkbox"/> ML2-12 |
| <input type="checkbox"/> ML2-13 | | | |
| <input type="checkbox"/> HML2-5 | <input type="checkbox"/> HML2-6 | <input type="checkbox"/> HML2-6.5 | <input type="checkbox"/> HML2-7 |
| <input type="checkbox"/> HML2-8 | <input type="checkbox"/> HML2-9 | <input type="checkbox"/> HML2-10 | <input type="checkbox"/> HML2-12 |
| <input type="checkbox"/> HML2-13 | | | |
|
 | | | |
| <input type="checkbox"/> ML3-5 | <input type="checkbox"/> ML3-6 | <input type="checkbox"/> ML3-6.5 | <input type="checkbox"/> ML3-7 |
| <input type="checkbox"/> ML3-8 | <input type="checkbox"/> ML3-9 | <input type="checkbox"/> ML3-10 | <input type="checkbox"/> ML3-12 |
| <input type="checkbox"/> ML3-13 | | | |
| <input type="checkbox"/> HML3-5 | <input type="checkbox"/> HML3-6 | <input type="checkbox"/> HML3-6.5 | <input type="checkbox"/> HML3-7 |
| <input type="checkbox"/> HML3-8 | <input type="checkbox"/> HML3-9 | <input type="checkbox"/> HML3-10 | <input type="checkbox"/> HML3-12 |
| <input type="checkbox"/> HML3-13 | | | |
|
 | | | |
| <input type="checkbox"/> ML4-5 | <input type="checkbox"/> ML4-6 | <input type="checkbox"/> ML4-6.5 | <input type="checkbox"/> ML4-7 |
| <input type="checkbox"/> ML4-8 | <input type="checkbox"/> ML4-9 | <input type="checkbox"/> ML4-10 | <input type="checkbox"/> ML4-12 |
| <input type="checkbox"/> ML4-13 | | | |
| <input type="checkbox"/> HML4-5 | <input type="checkbox"/> HML4-6 | <input type="checkbox"/> HML4-6.5 | <input type="checkbox"/> HML4-7 |
| <input type="checkbox"/> HML4-8 | <input type="checkbox"/> HML4-9 | <input type="checkbox"/> HML4-10 | <input type="checkbox"/> HML4-12 |
| <input type="checkbox"/> HML4-13 | | | |

OPTIONS:

Add options suffix number below to model number

- 5P 5" polyurethane casters, two with brakes
- Specify plastic laminate exterior
- 208/240V units are available

See reverse side for product specifications.



Lowerator® Enclosed Mobile Adjustube® Plate Dispensers

Models □ ML □ HML2,3,4

PRODUCT:

QUANTITY:

ITEM:

PRODUCT SPECIFICATION

Overall Dimensions: Units are 36 9/16" high.
See tables for variable lengths and widths.
Please contact factory for drawings.

FOB: Allen, TX 75013

Two-Stack Models – ML2 (Unheated) and HML2 (Heated)

Model Number	Dimensions L X W (in.)	Shipping Weight	China Size (in.)	Total Watts	Total Amps
ML2-5 HML2-5	23 5/8 x 15 3/8	92 lbs *106 lbs	Up to 5	420	3.5
ML2-6 HML2-6	23 5/8 x 15 3/8	94 lbs *118 lbs	5 1/8 to 5 3/4	480	4.0
ML2-6.5 HML2-6.5	23 5/8 x 15 3/8	95 lbs *119 lbs	5 7/8 to 6 1/2	540	4.5
ML2-7 HML2-7	23 5/8 x 15 3/8	96 lbs *120 lbs	6 5/8 to 7 1/4	600	5.0
ML2-8 HML2-8	30 3/8 x 15 3/8	98 lbs *122 lbs	7 3/8 to 8 1/8	660	5.5
ML2-9 HML2-9	30 3/8 x 15 3/8	102 lbs *124 lbs	8 1/4 to 9 1/8	760	6.3
ML2-10 HML2-10	30 3/8 x 15 3/8	104 lbs *150 lbs	9 1/4 to 10 1/8	840	7.0
ML2-12 HML2-12	32 7/8 x 17	110 lbs *170 lbs	10 1/4 to 11 7/8	1000	8.3
ML2-13 HML2-13	35 1/8 x 18	162 lbs *168 lbs	11 7/8 to 13	1080	9.1

*Heated units. Maximum capacity. Approximately 60 plates per tube. Boxed cubit ft. 17.49

Three-Stack Models – ML3 (Unheated) and HML3 (Heated)

Model Number	Dimensions L X W (in.)	Shipping Weight	China Size (in.)	Total Watts	Total Amps
ML3-5 HML3-5	30 3/8 x 17	113 lbs *147 lbs	Up to 5	630	5.3
ML3-6 HML3-6	30 3/8 x 17	115 lbs *149 lbs	5 1/8 to 5 3/4	720	6.0
ML3-6.5 HML3-6.5	34 5/8 x 17	116 lbs *150 lbs	5 7/8 to 6 1/2	810	6.8
ML3-7 HML3-7	34 5/8 x 17	117 lbs *150 lbs	6 5/8 to 7 1/4	900	7.5
ML3-8 HML3-8	40 1/4 x 18 7/8	121 lbs *151 lbs	7 3/8 to 8 1/8	990	8.3
ML3-9 HML3-9	40 1/4 x 18 7/8	126 lbs *152 lbs	8 1/4 to 9 1/8	1140	9.5
ML3-10 HML3-10	43 1/4 x 18 7/8	129 lbs *153 lbs	9 1/4 to 10 1/8	1260	10.5

*Heated units. Maximum capacity. Approximately 60 plates per tube. Boxed cubit ft. 26.93.

Four-Stack Models – ML4 (Unheated) and HML4(Heated)

Model Number	Dimensions L X W (in.)	Shipping Weight	China Size (in.)	Total Watts	Total Amps
ML4-5 HML4-5	25 1/8 x 24 7/8	131 lbs *178 lbs	Up to 5	840	7.0
ML4-6 HML4-6	25 1/8 x 24 7/8	133 lbs *180 lbs	5 1/8 to 5 3/4	960	8.0
ML4-6.5 HML4-6.5	25 1/8 x 24 7/8	135 lbs *181 lbs	5 7/8 to 6 1/2	1080	9.0
ML4-7 HML4-7	25 1/8 x 24 7/8	138 lbs *182 lbs	6 5/8 to 7 1/4	1200	10.0
ML4-8 HML4-8	30 3/8 x 29 1/8	144 lbs *183 lbs	7 3/8 to 8 1/8	1320	11.0
ML4-9 HML4-9	30 3/8 x 29 1/8	150 lbs *183 lbs	8 1/4 to 9 1/8	1520	12.7
ML4-10 HML4-10	30 3/8 x 29 1/8	152 lbs *1884 lbs	9 1/4 to 10 1/8	1680	14.0

*Heated units. Maximum capacity. Approximately 60 plates per tube. Boxed cubit ft.35.52.

*APW Wyott reserves the right to modify specifications or discontinue models without incurring obligation.

